



Miniature Power Relays Mini L

V23082-A1***


For dc operation, neutral, monostable
 1 changeover or 1 make contact
 Standard or sensitive
 Immersion cleanable
 Printed circuit terminals

VDE, UL

Approx. weight 12 g



ECR0657-T




All holes \varnothing 1,3 mm

Mounting hole layout
 View from the wiring side


Base terminals

1 changeover contact



ECR0784-W

1 make contact



ECR0785-S

Contact ratings:

Max. switching voltage	300 Vac/250 Vdc
Max. switching current	10 A (5 A for sensitive version)
Max. continuous current max.	10 A (bis 70 °C)
Max. power rating	40 ... 180 W (voltage-dependent) 2500 VA (1250 VA for sensitive version)
Contact material:	Silver, gold-flashed or silver cadmium oxide

Miniature Power Relays Mini L

Rated volt- age	Voltage range at 20 °C	Coil resistance at 20 °C ± 10 % Ω	Ordering code	DU Price each			
				Pcs	DU+	100+	500+
standard, 1 changeover contact, contact material silver, gold-flashed							
12	9,4 ... 26	320	V23082-A1005-A101	30			
24	18,8 ... 52	1250	V23082-A1007-A101	30			
standard, 1 changeover contact, contact material silver cadmium oxide							
12	9,4 ... 26	320	V23082-A1005-A401	30			
24	18,8 ... 52	1250	V23082-A1007-A401	30			
standard, 1 make contact, contact material silver, gold-flashed							
12	9,4 ... 26	320	V23082-A1005-A102	30			
24	18,8 ... 52	1250	V23082-A1007-A102	30			
standard, 1 make contact, contact material silver cadmium oxide							
12	9,4 ... 26	320	V23082-A1005-A402	30			
24	18,8 ... 52	1250	V23082-A1007-A402	30			
sensitive, 1 changeover contact, contact material silver cadmium oxide							
12	9,3 ... 28	400	V23082-A1205-A401	30			
24	18,5 ... 56	1600	V23082-A1207-A401	30			
sensitive, 1 make contact, contact material silver cadmium oxide							
12	9,3 ... 28	400	V23082-A1205-A402	30			
24	18,5 ... 56	1600	V23082-A1207-A402	30			